



Super Flex - 8 Strand

Dia. / mm	Dia./ inch	Cir / inch	Wt. Per 220 Mtrs. in Kgs.	Wt. Per 200 Mtrs. in Kgs.	Wt. Per Wt. Per 220 Mtrs. in Lbs	Wt. Per 200 Mtrs. in Lbs	Mtr/ Kg	Feet/ Kg	MBL / kgf	MBL / LBs	MBL / KN
517	40	1-5/85	5	192.50	175	423.50	385	1.14	3.75	34200	34200
517	44	1-3/4	5-1/2	228.80	208	503.36	457	0.96	3.15	40800	40800
517	48	1-15/16	6	264	240	580.80	528	0.83	2.73	47400	47400
517	52	2-1/16	6.5	310.20	282	682.44	620.40	0.71	2.33	55500	55500
517	56	2-1/4	7	345.40	314	759.88	690.80	0.64	2.09	63200	63200
517	60	2-3/8	7.5	402.60	366	885.72	805.20	0.55	1.79	72400	72400
517	64	2-1/2	8	453.20	412	997.04	906.40	0.49	1.59	81600	81600
517	68	2-15/16	8.5	510.40	464	1122.88	1020.80	0.43	1.41	91800	91800
517	72	2-7/8	9	567.60	516	1248.72	1135.20	0.39	1.27	102000	102000
517	76	3	9.5	622.60	566	1369.72	1245.20	0.35	1.16	112000	112000
517	80	3-1/4	10	701.80	638	1543.96	1403.60	0.31	1.03	125000	125000
517	88	3-15/16	11	836	760	1839.20	1672	0.26	0.86	148000	148000
517	96	3-3/4	12	983.40	894	2163.48	1966.80	0.22	0.73	174000	174000
517	104	4-1/2	13	1155	1050	2541	2310	0.19	0.62	198300	198300
517	112	1-7/8	14	-	1254	-	2758.80	0.18	0.58	230800	230800
517	120	5	15	-	1120	-	2464	0.20	0.64	263000	263000