



8x19 FC Çelik Halat

| Halat Çapı / mm | Birim Ağırlık kg/m | Minumum Kopma Kuvveti 1770 N/mm ² IPS | Minumum Kopma Kuvveti 1960 N/mm ² EIPS |
|-----------------|-----------------------|--|--|
| 8 | 0,22 | 33,2 | 36,8 |
| 9 | 0,28 | 42 | 46,5 |
| 10 | 0,34 | 51,9 | 57,4 |
| 11 | 0,41 | 62,8 | 69,5 |
| 12 | 0,49 | 74,7 | 82,7 |
| 13 | 0,58 | 87,6 | 97,1 |
| 14 | 0,67 | 101,6 | 112,6 |
| 15 | 0,77 | 117 | 129 |
| 16 | 0,87 | 133 | 147 |
| 17 | 0,98 | 150 | 166 |
| 18 | 1,1 | 168 | 186 |
| 19 | 1,23 | 187 | 207 |
| 20 | 1,36 | 207 | 230 |
| 21 | 1,5 | 229 | 253 |
| 22 | 1,65 | 251 | 278 |
| 23 | 1,8 | 274 | 304 |
| 24 | 1,96 | 299 | 331 |
| 25 | 2,13 | 324 | 359 |
| 26 | 2,3 | 351 | 388 |
| 27 | 2,48 | 378 | 419 |
| 28 | 2,67 | 407 | 450 |
| 29 | 2,86 | 436 | 483 |
| 30 | 3,06 | 467 | 517 |
| 31 | 3,27 | 498 | 552 |
| 32 | 3,48 | 531 | 588 |
| 33 | 3,7 | 565 | 625 |
| 34 | 3,93 | 600 | 664 |
| 35 | 4,17 | 635 | 703 |
| 36 | 4,41 | 672 | 744 |
| 37 | 4,66 | 710 | 786 |
| 38 | 4,91 | 749 | 829 |
| 39 | 5,17 | 789 | 873 |

DATA SHEET

| Halat Çapı / mm | Birim Ağırlık kg/m | Minumum Kopma Kuvveti 1770 N/mm ² IPS | Minumum Kopma Kuvveti 1960 N/mm ² EIPS |
|-----------------|-----------------------|--|--|
| 40 | 5,44 | 830 | 919 |
| 41 | 5,72 | 872 | 965 |
| 42 | 6 | 915 | 1013 |
| 43 | 6,29 | 959 | 1062 |
| 44 | 6,58 | 1004 | 1112 |
| 45 | 6,89 | 1050 | 1163 |
| 46 | 7,19 | 1097 | 1215 |
| 47 | 7,51 | 1146 | |
| 48 | 7,83 | 1195 | |
| 49 | 8,16 | 1245 | |
| 50 | 8,5 | 1297 | |
| 51 | 8,84 | 1349 | |
| 52 | 9,19 | 1402 | |

