


8x19 IWRC Çelik Halat

Halat Çapı / mm	Birim Ağırlık kg/m	Minumum Kopma Kuvveti 1770 N/mm ² IPS	Minumum Kopma Kuvveti 1960 N/mm ² EIPS
8	0,26	40,3	44,7
9	0,33	51	56,5
10	0,41	63	69,8
11	0,49	76,2	84,4
12	0,59	90,7	100,5
13	0,69	106	118
14	0,8	124	137
15	0,92	142	157
16	1,04	161	179
17	1,18	182	202
18	1,32	204	226
19	1,47	227	252
20	1,63	252	279
21	1,8	278	308
22	1,97	305	338
23	2,15	333	369
24	2,34	363	402
25	2,54	394	436
26	2,75	426	472
27	2,97	459	509
28	3,19	494	547
29	3,42	530	587
30	3,66	567	628
31	3,91	606	671
32	4,17	645	715
33	4,43	686	760
34	4,71	728	807
35	4,99	772	855
36	5,28	817	904
37	5,57	863	955
38	5,88	910	1008
39	6,19	958	1061

DATA SHEET



Halat Çapı / mm	Birim Ağırlık kg/m	Minumum Kopma Kuvveti 1770 N/mm2 IPS	Minumum Kopma Kuvveti 1960 N/mm2 EIPS
40	6,51	1008	1173
41	6,84	1059	1231
42	7,18	1112	1290
43	7,53	1165	1351
44	7,88	1220	1413
45	8,24	1276	1476
46	8,61	1333	
47	8,99	1392	
48	9,38	1452	
49	9,77	1513	
50	10,18	1575	
51	10,59	1639	
52	11,01	1704	