



19x7 IWRC Çelik Halat

Halat Çapı / mm	Birim Ağırlık kg/m	Minumum Kopma Kuvveti 1770 N/mm ² IPS	Minumum Kopma Kuvveti 1960 N/mm ² EIPS
4	0,064	9,3	
5	0,1	14,5	
6	0,145	20,9	
7	0,197	28,4	
8	0,257	37,2	
9	0,326	47	
10	0,401	58,1	64,3
11	0,485	70,2	77,8
12	0,577	83,6	92,6
13	0,678	98,1	108,6
14	0,786	113,8	126
15	0,902	131	145
16	1,027	149	165
17	1,159	168	186
18	1,299	188	208
19	1,448	210	232
20	1,604	232	257
21	1,768	256	284
22	1,941	281	311
23	2,121	307	340
24	2,31	334	370
25	2,506	363	402
26	2,711	392	435
27	2,923	423	469
28	3,144	455	504
29	3,372	488	541
30	3,609	523	579
31	3,854	558	618
32	4,106	594	658
33	4,367	632	700
34	4,636	671	743
35	4,912	711	788

DATA SHEET

Halat Çapı / mm	Birim Ağırlık kg/m	Minumum Kopma Kuvveti 1770 N/mm ² IPS	Minumum Kopma Kuvveti 1960 N/mm ² EIPS
36	5,197	752	833
37	5,49	795	880
38	5,79	838	928
39	6,099	883	977
40	6,416	929	1027

