



Polyamide / Nylon Rope - 12 Strand

Dia. mm	Dia. Inch	Cir. inch	Wt.Per 220 Mtrs. in Kgs.	Wt Per 200 Mtrs. in Kgs.	Wt.Per 220 Mtrs. in Lbs.	Wt.Per 200 Mtrs. in Lbs.	Mtr/kg	Feet/kg	MBL / kgf	MBL / Lbs	MBL / KN
52	2-1/16	6-1/2	387	351.82	851	773.64	0.57	1.86	54000	118800	118800
56	2-1/4	7	449	408.18	988	898.18	0.49	1.61	61200	134640	134640
60	2-3/8	7-1/2	512	465.45	1126	1023.64	0.43	1.41	70400	154880	154880
64	2-1/2	8	579	526.36	1274	1158.18	0.38	1.25	79200	174240	174240
68	2-15/16	8-1/2	666	605.45	1465	1331.82	0.33	1.08	89000	195800	195800
72	2-7/8	9	739	671.82	1626	1478.18	0.30	0.98	98900	217580	217580
76	3	9-1/2	822	747.27	1808	1643.64	0.27	0.88	110000	242000	242000
80	3-5/32	10	913	830	2009	1826.36	0.24	0.79	121000	266200	266200
84	3-1/2	10-1/2	1000	909.09	2200	2000	0.22	0.72	132000	290400	290400
88	3-7/16	11	1100	1000	2420	2200	0.20	0.66	144100	317020	317020
92	3-7/8	11-1/2	1110	1009.09	2686	2441.82	0.20	0.65	157000	345400	345400
96	3-13/16	12	1339	1217	2945	2677	0.16	0.52	169000	371800	371800
100	3-15/16	12-3/8	1420	1290.91	3124	2840	0.15	0.49	176000	387200	387200
104	4-1/2	13	-	1400	-	3080	0.14	0.45	181300	398860	398860
112	1-7/8	14	-	1304	-	2868	0.12	0.39	208000	457600	457600
120	5	15	-	1403	-	3086	0.10	0.32	238075	523767	523767